



exposure to this material.

Contact with skin or eyes: Skin and eye irritant, Direct & prolonged contact with the liquid may cause stinging, tearing, redness, swelling of the eyes and redness, burning, drying and cracking of skin.

Absorbed through skin: Symptoms of toxicity are not anticipated by this route alone under normal conditions of use. Persons with pre-existing skin disorders may be more susceptible to the effects of this material.

Swallowed: Ingestion of excessive quantities may cause irritation of the digestive tract. Signs of nervous system depression. ASPIRATION HAZARD- This material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

#### HEALTH EFFECTS OR RISKS FROM EXPOSURE -

Acute: Skin, eye, and respiratory tract irritation.

Chronic: Nervous system damage.

#### FIRST AID: EMERGENCY PROCEDURES -

Eye Contact: For direct contact hold eyelids apart and flush with clean water for at least 15 minutes.

Skin Contact: Remove contaminated clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention.

Inhaled: If respiratory symptoms or other symptoms of exposure develop, move victim away from source of exposure and into fresh air. If symptoms persists, seek medical attention. If breathing difficulties develop oxygen should be administered by qualified personnel. Seek medical attention.

Swallowed: Aspiration hazard. Do not give anything by mouth, because this material can enter lungs and cause severe lung damage. If victim is drowsy or unconscious, place on the left side with the head down. Seek medical attention.

COMMENTS: This material has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA. Overexposure to this material or its component has been found to cause the following in laboratory animals; Anemia, Liver abnormalities, Kidney damage, Eye damage, and also overexposure to this material or its component has been suggested as a cause of human cardiac Abnormality. Xylene an ingredient in this product has been found to cause harm to the fetus in the laboratory animal studies. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as solvent or painters' syndrome). Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

#### VI. REACTIVITY DATA

Stability: Stable under ordinary use & storage.

Incompatibility (materials to avoid): Strong oxidizing and reducing agents.

Hazardous Decomposition products (including combustion products): Carbon dioxide and/or carbon monoxide.

Hazardous polymerization: Will not occur

#### VII. SPILL, LEAK, AND DISPOSAL PROCEDURES

Spill response procedures: Stay upwind and away from spill. Keep all sources of ignition away from spill. If spill is indoors, ventilate area of spill. A universal type foam may be used to suppress vapors. Keep out of drains, sewers, or waterway. Use sand or other appropriate absorbing inert material to dam and contain spill. Do not flush area with water. Preparing wastes for disposal: Dispose in accordance with Local, County, State and Federal regulations.

#### VIII. SPECIAL HANDLING INFORMATION

Ventilation and engineering controls: If current ventilation practices are not adequate to maintain airborne concentrations below established exposure limits, additional ventilation or exhaust systems may be required. Where explosive mixtures may be present, electrical systems safe for such locations must be used.

Respiratory Protection: The use of respiratory protection is advised when concentrations exceed the established exposure limits. Depending on the airborne concentrations, use a respirator or gas mask with appropriate cartridges and canisters (NIOSH approved, if available) or supplied air equipment.

Eye Protection: Approved eye protection to safeguard against potential eye, injury is recommended.

Gloves: The use of nitrile gloves is advised to prevent skin contact and possible irritation.

Other clothing and equipment: It is suggested that a source of clean water be available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.

Work practices, hygienic practices: Practice personal cleanliness by prompt removal of solvent in contact with skin. Train all employees in special handling procedures prior to working with this product.

**OTHER HANDLING AND STORAGE REQUIREMENTS:**

Keep containers tightly closed. Keep containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. Use good personal hygiene practice. "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition; they may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged and promptly shipped to the supplier or a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

HURST CHEMICAL COMPANY furnishes Material Safety Data Sheets based upon information from raw material suppliers. This information is provided in compliance with Federal Regulation 29CFR 1910. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.

Prepared By: A. O. KORKIN, Ph.D.