



MATERIAL SAFETY DATA SHEET

I. PRODUCT INFORMATION

Trade Name: Metal Plate Cleaner and Desensitizer 328
Chemical names, common names: Complex Inorganic and Salt Mixture
Manufacturer's Name: HURST CHEMICAL COMPANY
Address: 2500 San Fernando Road, Los Angeles, CA. 90065
DOT CLASSIFICATION: (Not Regulated)
For Product Information, call : (323) 223-4121
FOR EMERGENCY, CALL CHEMTREC, 24 HOUR: 800 424-9300

II. HAZARDOUS INGREDIENTS

<u>Chemical Names</u>	<u>CAS Number</u>	<u>Exposure Limits in Air</u> <u>ACGIH (TWA)</u>	<u>OSHA (PEL)</u>
2-Butoxyethanol	111-76-2	25 ppm	25 ppm

Section IIA - This product contains the following chemicals subject to reporting requirements of SARA 313 and 40 CFR 372.

<u>Listed Ingredients</u>	<u>CAS Number</u>	<u>Weight % Range</u>
2-Butoxyethanol	111-76-2	3 - 4

III. PHYSICAL PROPERTIES

Vapor density (air = 1): <1
Solubility in water: 100%
Evaporation rate (Bu Ac = 1): <1
Appearance and odor: Clear pink liquid with lemon odor.
Volatile Organic Content (VOC,EPA Method 24): 45.4 gm/l or 0.36 lb/gal

Specific Gravity: 1.02
VOC Composite Partial Pressure, mm Hg at 20°C: <1
Boiling Range °F: 212
Density lb/gal: 8.5
PH = 11.8

IV. FIRE AND EXPLOSION

<u>HAZARD RANKING</u>			
HMIS	Health Hazard=1	0=Least	4=Extreme
HAZARD	Flammability=0	1=Slight	B = Gloves and Safety goggles
CLASS	Reactivity= 0	2=Moderate	
	Other = B	3 = High	

Flash Point °F: >200
Flammable limits in air,volume%: lower 1.2 upper 10.6
Fire extinguishing materials: No water spray Yes dry chemical Y carbon dioxide No other Y foam

Special firefighting procedures: Solvent vapors exposed to open flame can become combustible under certain conditions; then use foam, dry chemical or CO2 to extinguish.

Unusual fire and explosion hazard: Keep work areas free of hot metal surfaces and other sources of ignition.

V. HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE FOR EACH POTENTIAL ROUTE OF EXPOSURE -

Inhaled: Breathing vapors or mists may cause irritation of the nose and throat and kidney damage.
Contact with skin or eyes: This product is eye and skin irritant. Prolonged eye and skin contact may cause permanent eye injury and skin damage.
Absorbed through skin: This material is toxic when absorbed through skin.
Swallowed: Swallowing large quantities of this material may cause burning of the mouth, throat, and digestive tract accompanied by severe pain.

HEALTH EFFECTS OR RISKS FROM EXPOSURE -

Acute: Eye and skin damage.
Chronic: May result in areas of destruction of skin tissue or primary irritant Dermatitis.

FIRST AID: EMERGENCY PROCEDURES -

Eye Contact: Immediately flush eyes with lots of water for 15 minutes. get immediate medical attention.

Skin Contact: Immediately wash skin with lots of water. Remove contaminated clothing and shoes; wash before use. Get medical attention if irritation persists.

Inhaled: Remove to fresh air. If symptoms of over exposure occurs seek medical attention.

Swallowed: Do not induce vomiting, give lots of water or milk. Get immediate medical attention.

COMMENTS: This product has not been identified as a carcinogen by NTP, IARC or OSHA.

One of the ingredients (2-Butoxyethanol) in this product caused blood disorders, (resulting in Kidney, Liver and Spleen damage) in long term studies in laboratory animals.

MEDICAL CONDITION AGGRAVATED BY EXPOSURE: Pre-existing blood disorders may be aggravated by exposure to this material.

RECOMMENDATIONS TO PHYSICIAN- If symptoms if over exposure occurs, obtain blood glucose and complete neurological examination.

VI. REACTIVITY DATA

Stability: Stable under ordinary use & storage.

Incompatibility (materials to avoid): Oxidizers and strong acids. Prolonged contact with aluminum, copper, tin, lead or zinc may liberate flammable hydrogen gas.

Hazardous Decomposition products (including combustion products): Carbon monoxide and carbon dioxide.

Hazardous polymerization: Will not occur

VII. SPILL, LEAK, AND DISPOSAL PROCEDURES

Spill response procedures: For large spills, contain by diking with non-combustible absorbent material and carefully neutralize with diluted hydrochloric acid. Keep the materials out of sewers, storm drains, surface waters and soil.

Preparing wastes for disposal: Dispose of contaminated product and materials used in cleaning up spills or leaks according to Local, State and Federal regulations.

VIII. SPECIAL HANDLING INFORMATION

Ventilation and engineering controls: Normal shop ventilation is adequate, floor ventilation is preferred.

Respiratory Protection: In working atmosphere where mist is prevalent, use NIOSH-approved air-purifying respirator with mist filter.

Eye Protection: Use safety goggles where solvent splashes are expected.

Gloves: Use nitrile gloves to prevent repeated or prolonged skin contact.

Other clothing and equipment: Eye wash and quick drench shower facilities should be available in the work area.

Thoroughly clean shoes and wash contaminated clothing before reuse.

Work practices, hygienic practices: Practice personal cleanliness by prompt removal of solvent in contact with skin. Train all employees on special handling procedures prior to working with this product.

OTHER HANDLING AND STORAGE REQUIREMENTS:

Keep containers tightly closed. Keep containers cool, dry and away from sources of ignition. Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. Use good personal hygiene practice.

HURST CHEMICAL COMPANY furnishes Material Safety Data Sheets based upon information from raw material suppliers. This information is provided in compliance with Federal Regulation 29CFR 1910.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.

Prepared By: A. O. KORKIN, Ph.D.