

LITHCO MATERIAL SAFETY DATA SHEET

SECTION I: PRODUCT IDENTIFICATION

TRADE NAME (as labeled) Lithco Sun Glide™ Silicone Release Spray

MANUFACTURER'S NAME: Lithco, Inc. • 9449 Jefferson Blvd. • Culver City, CA 90232-2913

PHONE NUMBER FOR ADDITIONAL INFORMATION: (310) 559-7770 or (800) 454-8426

FAX NUMBER FOR ADDITIONAL INFORMATION: (310) 559-6908 or (888) 454-8426

EMERGENCY INFORMATION: For chemical emergency, spill, leak, fire, exposure or accident call Infotrac, day or night, at (800) 535-5053.

DATE PREPARED OR REVISED: 7-5-02 (Replaces 10-1-01)

PREPARED BY (optional):

SECTION II: HAZARDOUS INGREDIENTS

Chemical Names	CAS Numbers	%	EXPOSURE LIMITS		
			ACGIH TLV	OSHA PEL	OTHER
Pentane	109-66-0		600 ppm	600 ppm	N/A
Hydrocarbon propellant	68476-85-7		1000 ppm	1000 ppm	N/A
Silicone oil	63148-62-9		5 mg/m ³ mist	5 mg/m ³ mist	N/A
Isoparaffinic solvent	64742-48-9		300 ppm	300 ppm	N/A
Butyl Alcohol	71-36-3		100 ppm	100 ppm	N/A

HMS RATING: Health: 1 Fire: 4 Reactivity: 0 Personal protection: B

SECTION III: PHYSICAL PROPERTIES

VAPOR DENSITY (AIR = 1): > 1

MELTING POINT/RANGE: N/A

SPECIFIC GRAVITY: 0.6

BOILING POINT/RANGE: -44 - 154 °F

SOLUBILITY IN WATER: negligible

EVAPORATION RATE (BuAc = 1): >1

VAPOR PRESSURE, mm Hg @ 20 degrees C: 105 psi @ 130°F **APPEARANCE AND ODOR:** Clear, oily liquid, mild odor

This product contains 98 % VOC by formulation. VOC = 306 GM/CAN.

This product is not photochemically reactive.

SECTION IV: FIRE AND EXPLOSION

FLASH POINT, degrees F. (give method): <20°F TCC

AUTO-IGNITION TEMPERATURE, degrees F.: N.D.

FLAMMABLE LIMITS IN AIR (VOLUME %), LOWER 1.9 % **UPPER** 8.5 %

FIRE EXTINGUISHING MATERIALS:

WATER SPRAY:	FOAM:	CARBON DIOXIDE: XXX	DRY CHEMICAL: XX	OTHER: N/A
--------------	-------	---------------------	------------------	------------

SPECIAL FIRE FIGHTING PROCEDURES: Fire fighting personnel should wear full bunker gear with NIOSH approved SCBA.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool exposed containers with water fog to prevent explosions. At elevated temperatures (over 130° F), containers may vent, rupture or burst.

Page 2 of 4 Lithco Sun Glide™ Silicone Spray

SECTION V: HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE FOR EACH POTENTIAL ROUTE OF EXPOSURE

INHALED: Vapors may be mildly irritating to lungs.

CONTACT WITH SKIN OR EYES: May cause mild irritation to skin and eyes.

ABSORBED THROUGH SKIN: Can be absorbed through the skin in harmful amounts.

SWALLOWED: Not an expected route of exposure.

HEALTH EFFECTS OR RISKS FROM EXPOSURE (Explain in lay terms)

ACUTE: Mild irritation to skin, eyes and respiratory system.

CHRONIC: Inhalation of vapor can produce central nervous system depression characterized by dizziness, headache, nausea, cardiac and/or respiratory depression, chemical pneumonia.

FIRST AID EMERGENCY PROCEDURES

EYE CONTACT: Flush eyes for at least 15 minutes with running water while holding eyelids open. Get medical attention.

SKIN CONTACT: Remove contaminated clothing. Wash affected area with soap and water. Seek medical attention if irritation persists. Do not wear contaminated clothing until properly laundered.

INHALED: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration or CPR if not breathing. Seek medical attention.

SWALLOWED: Do not induce vomiting. If vomiting occurs, keep victim's head below knees to prevent aspiration into lungs. Get immediate medical attention.

SUSPECTED CANCER AGENT?

NO. THIS PRODUCT'S INGREDIENTS ARE NOT FOUND IN THE LISTS BELOW.

YES. FEDERAL OSHA NTP IARC

California employers using CAL/OSHA regulated carcinogens must register with CAL/OSHA. The CAL/OSHA and Federal OSHA carcinogen lists are similar.

CALIFORNIA PROP. 65 STATEMENT

THIS PRODUCT DOES NOT CONTAIN CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR CAUSE REPRODUCTIVE HARM.

PRE-EXISTING MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known at time of preparation.

SECTION VI: REACTIVITY DATA

PRODUCT IS XXX STABLE ____ UNSTABLE

CONDITIONS TO AVOID: Avoid contact with heat, sparks and open flame.

INCOMPATIBILITY (materials to avoid): Strong oxidizing agents, sources of ignition.

HAZARDOUS DECOMPOSITION PRODUCTS, INCLUDING COMBUSTION: Carbon monoxide, carbon dioxide and unburned hydrocarbons

HAZARDOUS POLYMERIZATION ____ **MAY OCCUR** XXX **WILL NOT OCCUR.**

CONDITIONS TO AVOID: None under normal product use.

SECTION VII: SPILL, LEAK AND DISPOSAL PROCEDURES

SPILL RESPONSE PROCEDURES, INCLUDING EMPLOYEE PROTECTION: Extinguish all sources of ignition. Contain spill. Wear SCBA for airborne concentrations above TLV. Use sparkproof tools during clean-up. Soak up with inert absorbent.

PREPARING WASTES FOR DISPOSAL (containers, neutralization, etc.): Place in non-leaking containers suitable for material and certified for transporting hazardous waste.

NOTE: DISPOSE OF ALL WASTES IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION VIII: SPECIAL HANDLING INFORMATION

VENTILATION AND ENGINEERING CONTROLS: Provide ventilation to keep airborne concentration below TLV.

RESPIRATORY PROTECTION (TYPE): NIOSH/MCA approved for organic vapors for concentrations above TLV.

EYE PROTECTION (TYPE): Splashproof chemical goggles.

GLOVES (SPECIFY MATERIAL): Neoprene, nitrile or PVC.

OTHER CLOTHING AND EQUIPMENT: Eyewash station and safety shower should be provided.

WORK PRACTICES, HYGIENIC PRACTICES: Wash hands thoroughly after use and before eating, drinking, smoking or using the toilet.

OTHER HANDLING AND STORAGE REQUIREMENTS: Keep containers closed when not in use. Do not use near sources of ignition. Avoid prolonged or repeated contact with skin or breathing of vapors. Keep from children. For industrial use only.

PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: Use protective gear as indicated above. Do not start electrical equipment in presence of vapors.

Page 4 of 4 Lithco Sun Glide™ Silicone Spray

SECTION IX: SHIPPING INFORMATION

FULL DOT SHIPPING NAME: ORM-D

DOT HAZARD CLASS: N/A **PACKING GROUP:** N/A **UN/NA NUMBER:** None assigned

SECTION X: ENVIRONMENTAL STATEMENT

THIS PRODUCT IS NOT SUBJECT TO REPORTING ACCORDING TO SARA, TITLE III (SUPERFUND AMENDMENT).

CERCLA Information (40CFR302.4)

Releases of this material to air, land or water are not reportable to the National Responses Center under the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

RCRA Information

Prior to disposal, consult your environmental contact to determine if TCLP (Toxicity Characteristic Leaching Procedure, EPA Test Method 1311) reference 40CFR261 applies to this product.

Chemical \\control Law Status

All components of this product are listed or excluded from listing on the U.S. Toxic Substance Control Act (TSCA) Chemical Substance Inventory.

Information contained in this safety data sheet is drawn from recognized sources and is believed to be accurate and correct as of the date of issue. It is presented for your evaluation of the suitability of the product and for compliance with federal and state regulations. No claims are made for the accuracy, completeness and reliability of the information contained herein.