1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: General Use:	Print Shield Spray varnish sealer for ink jet prints
Product Description:	Aerosol spray sealer
Manufactured For:	Premier Imaging Products
	121 Lombard Street
	Oxnard
	CA 93030
	USA
TELEPHONE No.:	805 983 1472

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	% W t.	CAS No.	EEC No.	Symbol	R	EXPOSURE Long Term (8Hr)		E LIMITS Short Term (15 mins)	
						ppm	mg/m ³	ppm	mg/m ³
Isopropyl Alcohol	40-60	67-63-0	200-661-7	F	11, 36, 67	400	999	500	1250
Dimethyl Ether	40-60	115-10-6	204-065-8	F+	12	400	766	500	958
n-Butyl Acetate	1-3	123-86-4	204-658-1	-	10, 66, 67	150	742	200	966

Remaining ingredients not considered hazardous under CHIP regulations

3. HAZARDS IDENTIFICATION

Extremely Flammable. Vapour harmful. The principal safety and health hazards when using the product are due to inhalation of isopropanol vapors. There is also a risk of ignition of the spray should it pass through or on an ignition source. Inhalation may occur while spraying the product or during the drying process. If the product is used with adequate ventilation, risk of excessive inhalation is eliminated.

4. FIRST AID MEASURES

- EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation persists.
- **SKIN**: Wash with soap and water. Get medical attention if irritation or rash develops. Remove and launder contaminated clothing before reuse.
- INGESTION: If fully conscious, drink plenty of water. Induce vomiting. Get medical attention.
- INHALATION: Remove to fresh air. If not breathing, apply artificial respiration. Get immediate medical attention
- ADVICE TO PHYSICIAN : Treat symptoms.

5. FIRE FIGHTING MEASURES

- EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, foam for alcohols, water fog/ spray.
- FIRE/EXPLOSION HAZARDS: Containers are under pressure. Exposure to high heat may result in explosion.
- FIRE FIGHTING MEASURES: Wear a self-contained breathing apparatus and full protective gear. Cool cans with water.
- NFPA HAZARD CODES: Health/Flammability/Reactivity 2 4 1

6. ACCIDENTAL RELEASE MEASURES

Evacuate area. Provide adequate ventilation. Contain spill to a small area. Flush away from ignition sources with water. Pick up with absorbent material and transfer to suitable container for disposal. Keep out of sewers, streams and waterways.

7. HANDLING AND STORAGE

Do not puncture or crush container, even when empty. Keep away from open flames and sparks. Store above 0° C (32° F) and below 49° C (120° F). Do not store in direct sunlight.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels. Use a fume hood if PEL/TLV may be exceeded.
- PERSONAL PROTECTION
- **RESPIRATORY PROTECTION**: For most conditions no respiratory protection should be needed. If Exposure limit is exceeded, wear an approved organic respirator.
- PROTECTIVE GLOVES: Not normally required. Wear chemical resistant gloves, if skin contact may occur.
- EYE PROTECTION: Wear safety glasses or goggles.

<u>م</u> ۲	PHYSICAL AND CHEMICAL PR						
9. F * * * * * * * *	PHYSICAL AND CHEMICAL PR PHYSICAL STATE: BOILING POINT: FLASH POINT: AUTOIGNITION TEMP.: VAPOUR PRESSURE: SOLUBILITY IN WATER: FREEZING POINT: SPECIFIC GRAVITY: pH: VAPOUR DENSITY: EVAPORATION RATE: % VOLATILE (BY VOLUME) FLAMMABLE LIMITS:	Clear low viscosit 82.5°C (181°F) (sity liquid with an alcohol odor. (Isopropanol) en cup (Product only) Upper: 12.7 (Isopropanol)				
10.	STABILITY AND REACTIVITY						
* * *	STABLE: INCOMPATIBILITY: HAZARDOUS DECOMPOSITI HAZARDOUS POLYMERISAT		Yes Strong Oxidizers, strong inorganic acids. May include oxides of carbon, nitrogen and other toxic fumes. Will not occur.				
11.	TOXICOLOGICAL INFORMAT	ION					
٠	PRIMARY ROUTE OF EXPOS	SURE: Inhalat	ation, skin and eye contact				
* * *	ACUTE EFFECTS: Eye contact may cause irritation. INHALATION: Inhalation in excess of PEL/TLV may result in dizziness and headache and in extreme cases, loss of consciousness. SKIN: Repeated or prolonged skin contact may cause skin irritation and defat the skin. CHRONIC EFFECTS: None expected from available data. CANCER INFORMATION: This product contains no ingredient that is listed on the IARC, NTP, or OSHA carcinogen lists.						
12.	ECOLOGICAL INFORMATION						
13	DISPOSAL CONSIDERATION	 S					
		-	Follow Federal, State, and local regulations.				
14.		•					
 TDG: Aerosol, 2.1, UN1950 IMDG: Aerosols, Class 2, UN1950, ERG No.12 IATA/CAO: Aerosols, Flammable, N.O.S., UN 1950 ARD/RID: Aerosol Dispensers, 2, 5°F ARD.UN1950 U.S. DOT: Consumer Commodity ORM-D for package weights more than 30 Kg Aerosols, Flammable, N.O.S., UN 							
15.	REGULATORY INFORMATION	N					
٠	EUROPEAN CLASSIFICATIO		ely flammable; R-Phrase - Extremely flammable; S-Phrase - keep away from				
٠	CANADIAN CLASSIFICATION	<u>N</u> : B-2: Fla	rces, no smoking. Flammable aerosol; R-Phrase - Flammable; S-Phrases - keep away from on, no smoking; Do not breathe spray; Use only in well ventilated areas.				
•	16. OTHER INFORMATION HMIS Rating : Health	: 2 Flamma	nability : 4 Reactivity : 1				
* * *	CERCLA/SUPERFUND,40 CF TOXIC SUBSTANCES CONTI SARA TITLE III, 313 CHEMIC CALIFORNIA PROPOSITION	ROL ACT (TSCA) ALS: 65:	Dimethyl Ether is reportable, 100 lbs (45.4 kg.). The ingredients of this product are all on the TSCA inventory list. None This product contains no chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.				

This information is based solely on the data provided by the suppliers of the materials used and/or recognized technical sources, not on the mixture itself and is believed to be correct as of this date. No warranty is expressed or implied regarding the accuracy of the data.