Safety Data Sheet

Classified in accordance 29 CFR 1910.1200

800-332-9000

866-836-8855

1. Product Identification Product Information: 100000562 Product Identifier: SPRAYWAY SW077 ALL PURPOSE DRY LUBRICANT & RELEASE AGENT Recommended Use: Lubricant Manufacturer/Importer/Distributor Information: PLZ CORP 2651 WARRENVILLE RD, STE 300 DOWNERS GROVE, IL 60515 US

Emergency Telephone:

2. Hazard(s) identification

Classification

Flammable Aerosol, category 1 Aspiration Hazard, category 1 Eye Irritation, category 2A STOT, single exposure, category 3, NE

Label elements

HAZARD PICTOGRAMS



SIGNAL WORD Danger

GHS HAZARD STATEMENTS

- H222 Extremely flammable aerosol.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

GHS PRECAUTIONARY STATEMENTS

Prevention	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust, fumes, gas, mist, vapours, or spray.
P264+P265	Wash hands thoroughly after handling. Do not touch eyes.

P271	Use only outdoors or in a well-ventilated area.
P280	Wear eye protection and face protection
Response	
P301+P316	IF SWALLOWED: Get emergency medical help immediately.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P319	Get medical help if you feel unwell.
P331	Do NOT induce vomiting.
P337+P317	If eye irritation persists: Get medical help.
Storage	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.
Disposal	
P501	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other Information	

None

3. Composition/Information on Ingredients

Mixtures

Chemical Identity	CAS Number	Content in Percent (%)*
Acetone	67-64-1	25-50
Propane	74-98-6	10-25
Butane	106-97-8	10-25
Naphtha, (Petroleum), Hydrotreated Light	64742-49-0	10-25
Distillates (Petroleum), Hydrotreated Light	64742-47-8	2.5-10
n-Heptane	142-82-5	2.5-10

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition Comments: Other components are not hazardous or are below required disclosure limits.

The exact concentration has been withheld as a trade secret.

4. First-aid Measures

SKIN CONTACT: Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

EYE CONTACT: Rinse immediately with plenty of water.

INHALATION: Move to fresh air.

INGESTION: Rinse mouth.

IMPORTANT SYMPTOMS: No data available

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: Get medical attention if symptoms occur.

5. Fire-fighting Measures

EXTINGUISHING MEDIA: Use fire-extinguishing media appropriate for surrounding materials.

UNSUITABLE EXTINGUISHING MEDIA: Do not use water jet as an extinguisher, as this will spread the fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: No data available

SPECIAL FIREFIGHTING PROCEDURES: No data available

6. Accidental Release Measures

PERSONAL PRECAUTIONS : Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Stop the flow of material, if this is without risk. Absorb with sand or other inert absorbent.

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages.

7. Handling and Storage

HANDLING: Keep away from sources of ignition - No smoking. Keep away from open flames, hot surfaces and sources of ignition. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

SAFE HANDLING ADVICE: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

STORAGE: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

NFPA 30B: Aerosol Level 3

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>TLV-TWA</u>	TLV-STEL	PEL-TWA	PEL-CEILING
250 ppm	500 ppm	1000 ppm	N.E.
N.E.	N.E.	1000 ppm	N.E.
N.E.	1000 ppm	N.E.	N.E.
N.E.	N.E.	100 ppm	N.E.
200 mg/m3	N.E.	N.E.	N.E.
400 ppm	500 ppm	500 ppm	N.E.
	250 ppm N.E. N.E. N.E. 200 mg/m3	250 ppm 500 ppm N.E. N.E. N.E. 1000 ppm N.E. N.E. 200 mg/m3 N.E.	250 ppm 500 ppm 1000 ppm N.E. N.E. 1000 ppm N.E. 1000 ppm N.E. N.E. 1000 ppm N.E. N.E. N.E. 100 ppm 200 mg/m3 N.E. N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

ENGINEERING CONTROLS: No data available.

Personal Protection

EYE/FACE PROTECTION: Wear goggles/face shield.

SKIN PROTECTION: No data available

RESPIRATORY PROTECTION: Seek advice from local supervisor. In case of inadequate ventilation use suitable respirator.

HYGIENIC PRACTICES: When using do not smoke. Observe good industrial hygiene practices.

9. Physical and Chemical Properties

Appearance:

••	
Physical State:	Liquid
Form:	Spray Aerosol
Color:	No data available
Odor:	No data available
Odor Threshold:	No data available
pH:	No data available
Freeze Point, °C:	No data available
Boiling Point, °C:	56
Flash Point, °C:	-104
Flammability (solid, gas):	No data available
Evaporation Rate:	No data available
Combustibility:	Supports Combustion
Explosive Limits, %:	0.2 - 12.8
Vapor Pressure @20°C, PSI:	50-70
Vapor Density:	No data available
Relative Density:	No data available
Solubility in Water:	No data available
Partition Coefficient, n-octanol/water:	No data available
Auto-Ignition Temperature, °C:	No data available
Decomposition temperature, °C:	No data available
Kinematic Viscosity:	No data available

10. Stability and Reactivity

REACTIVITY: No data available.

STABILITY: Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: No data available.

CONDITIONS TO AVOID: Avoid heat or contamination

INCOMPATIBILITY: No data available

HAZARDOUS DECOMPOSITION PRODUCTS: No data available.

11. Toxicological Information

Information on Likely Routes of Exposure

IMPORTANT SYMPTOMS: No data available

SKIN CONTACT EFFECTS: May cause irritation on prolonged or repeated contact.

EYE CONTACT EFFECTS: May cause slight irritation with tearing.

INHALATION EFFECTS: Inhalation of high concentrations of mists may cause irritation of the nose throat and upper respiratory tract.

INGESTION EFFECTS: Ingestion may cause irritation of the mucous membranes, esophagus and stomach.

CHRONIC HAZARDS: No data available

Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible, or confirmed human carcinogen by IARC, ACGIH, NTP or OSHA.

The following values are calculated based on chapter 3.1 of the GHS document. The product itself has not been tested.

ATE ORAL	7,638 mg/kg
ATE DERMAL	5,935 mg/kg
ATE INHALATION	Not classified for acute toxicity based on available data.

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below				
CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
67-64-1	Acetone	5,800 mg/kg	7,426 mg/kg	50.1 mg/l
74-98-6	Propane	5,000 mg/kg	5,000 mg/kg	100 mg/l
106-97-8	Butane	5000 mg/kg	5000 mg/kg	658 mg/L Rat
64742-49-0	Naphtha, (Petroleum), Hydrotreated Light	5,000 mg/kg	3,750 mg/kg	100 mg/l
64742-47-8	Distillates (Petroleum), Hydrotreated Light	5,000 mg/kg	2,000 mg/kg	>100 mg/l
142-82-5	n-Heptane	5,000 mg/kg	2,000 mg/kg	29.29 mg/l

N.I. = No Information

Skin Corrosion & Irritation:		
Product:		No data available
Serious Eye Damage & Irritation:		
Product:		No data available
Components:		
Acetone	67-64-1	Causes serious eye irritation.
Respiratory or Skin Sensitization:		
Product:		No data available
STOT-Single Exposure:		
Product:		No data available
Components:		
n-Heptane	142-82-5	May cause drowsiness or dizziness.
Acetone	67-64-1	May cause drowsiness or dizziness.
STOT-Repeated Exposure:		
Product:		No data available
Aspiration Hazard:		
Product:		No data available
Components:		
Naphtha, (Petroleum), Hydrotreated Light	64742-49-0	May be fatal if swallowed and enters airways.
n-Heptane	142-82-5	May be fatal if swallowed and enters airways.
Distillates (Petroleum), Hydrotreated Light	64742-47-8	May be fatal if swallowed and enters airways.
Carcinogenicity:		
Product		No data availabla

Product:

Reproductive Toxicity:	
Product:	No data available
Germ Cell Mutagenicity:	
Product:	No data available
12. Ecological Information	

ECOLOGICAL INFORMATION: No data available

PERSISTENCE: No data available

BIOACCUMULATE: No data available

MOBILITY IN SOIL: No data available

OTHER ECOLOGICAL: No data available

13. Disposal Information

DISPOSAL INFORMATION: Consult with your local, regional and federal agencies for information on proper disposal.

CONTAMINATED PACKAGING : Consult with your local, regional and federal agencies for information on proper disposal.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No data available

DOT

UN Number:	UN1950
Proper Shipping Name:	AEROSOLS, FLAMMABLE
Technical Name:	N/A
Hazard Class(es)	
Class:	2.1
Subsidiary Risk	N/A
Packing Group:	N/A
ΙΑΤΑ	
UN Number:	UN1950
Proper Shipping Name:	AEROSOLS, FLAMMABLE
Technical Name:	N/A
Hazard Class(es)	
Class:	2.1
Subsidiary Risk:	N/A
Packing Group:	N/A
IMDG	
UN Number:	UN1950
Proper Shipping Name:	AEROSOLS, FLAMMABLE
Technical Name:	N/A
Hazard Class(es)	
Class:	2.1
Subsidiary Risk:	N/A
Packing Group:	N/A

The classification shown In this section may be eligible for use of an exception, such as 'Limited Quantity', per the dangerous goods regulations. The shipper of this product should consult the applicable mode's regulation for the UN number displayed above to determine if any exceptions are available and may be utilized, at the shipper's discretion.

15. Regulatory Information

CHEMICAL INVENTORY STATUS:

TSCA DSL On or in compliance with the inventory

All ingredients in this product are listed on the DSL or are exempt.

CALIFORNIA PROPOSITION 65 CARCINOGENS AND REPRODUCTIVE TOXINS:

🕂 WARNING

Warning: This product may contain ingredients known to the state of California to cause Cancer or Reproductive Harm.

Chemical Name	CAS-No.
Toluene	108-88-3
n-Hexane	110-54-3
Ethyl Benzene	100-41-4
Benzene	71-43-2

16. Other Information

Revision Date:	9/1/2022
Datasheet produced by:	Regulatory Department
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

Legend

- N/A. Not Applicable, N.E. Not Established, N.D. Not Determined, N.I. No Information
- TLV Threshold Limit Values (TLVs®), as established by the American Conference of Governmental Industrial Hygienists (ACGIH®)
- PEL Permissible Exposure Limit, as established by the U.S. Occupational Safety and Health Administration (OSHA), as amended
- TSCA U.S. Toxic Substance Control Act
- DSL Canada Environmental Protection Act: Domestic Substance List

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

Revision Date: 9/1/2022