Safety Data Sheet

Classified in accordance 29 CFR 1910.1200

1. Product Identification

Product Information: 1000011778

Product Identifier: SPRAYWAY L3 MOLY PTFE LUBRICANT PROTECTANT

Recommended Use: Lubricant

Manufacturer/Importer/Distributor Information: PLZ Corp.

2651 WARRENVILLE RD, STE 300 DOWNERS GROVE, IL 60515

800-332-9000

Emergency Telephone: 866-836-8855

2. Hazard(s) identification

Classification

Flammable Aerosol, category 1 Aspiration Hazard, category 1 Skin Sensitizer, category 1 Eye Irritation, category 2A

Label elements

HAZARD PICTOGRAMS



SIGNAL WORD

Danger

GHS HAZARD STATEMENTS

H222 Extremely flammable aerosol.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

GHS PRECAUTIONARY STATEMENTS

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust, fumes, gas, mist, vapours, or spray.

P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

7706 Page 1 / 8

P280 Wear protective gloves, eye protection, and face protection

Response

P301+P310+P331 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

Storage

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Disposal

P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with

applicable laws and regulations, and product characteristics at time of disposal.

Other Information

None

3. Composition/Information on Ingredients

Mixtures

| Chemical Identity | CAS Number | Content in Percent (%)* |
|---|------------|-------------------------|
| Distillates (Petroleum), Hydrotreated Light | 64742-47-8 | 25-50 |
| Propane | 74-98-6 | 10-25 |
| Diethylene Glycol Monobutyl Ether | 112-34-5 | 2.5-10 |
| Oils, pine | 8002-09-3 | 1.0-2.5 |
| Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) | 4259-15-8 | 1.0-2.5 |
| Phosphorodithioic Acid, O,o-di-c1-14-alkyl Esters, Zinc Salts | 68649-42-3 | 1.0-2.5 |
| Distillates (Petroleum) Solvent-dewaxed Heavy Paraffinic | 64742-65-0 | 0.1-1.0 |

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition Comments: Other components are not hazardous or are below required disclosure limits.

The exact concentration has been withheld as a trade secret.

4. First-aid Measures

SKIN CONTACT: Remove contaminated clothing and wash the skin thoroughly with soap and water after work. Wash contact area thoroughly with soap and water. Get medical attention if irritation or rash develops or persists. Remove contaminated clothing. Launder clothing before re-use.

EYE CONTACT: Rinse immediately with plenty of water. Flush eyes with plenty of water for 15 minutes, while holding the eyelids apart. Check victim for contact lenses and remove if present. Get medical attention if irritation persists.

INHALATION: Move to fresh air.

INGESTION: Keep the victim calm and warm. Do NOT induce vomiting. If conscious, rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs. Get immediate medical attention.

IMPORTANT SYMPTOMS: Aspiration hazard: Harmful or fatal if swallowed. May cause severe eye irritation. May cause allergic skin reaction (sensitization.)

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED: Get medical attention if symptoms occur. Immediate medical attention is required for ingestion.

7706 Page 2 / 8

5. Fire-fighting Measures

EXTINGUISHING MEDIA: Use fire-extinguishing media appropriate for surrounding materials.

UNSUITABLE EXTINGUISHING MEDIA: Do not use water jet as an extinguisher, as this will spread the fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Extremely flammable aerosol. Contents under pressure. Keep away from ignition sources and open flames. Prolonged exposure to temperatures above 120°F may cause cans to burst. Vapors may travel considerable distance to a source of ignition and flash back. Combustion may produce carbon dioxide and carbon monoxide.

SPECIAL FIREFIGHTING PROCEDURES: No data available

Accidental Release Measures

PERSONAL PRECAUTIONS: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Leaking cans should be placed in a plastic bag or open pail away from ignition sources until the pressure has dissipated. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal.

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages.

7. Handling and Storage

HANDLING: Keep away from sources of ignition - No smoking. Keep away from open flames, hot surfaces and sources of ignition. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

SAFE HANDLING ADVICE: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

STORAGE: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

NFPA 30B: Aerosol Level 3

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

| Chemical Name | TLV-TWA | TLV-STEL | PEL-TWA | PEL-CEILING |
|---|-----------|----------|----------|-------------|
| Distillates (Petroleum), Hydrotreated Light | 200 mg/m3 | N.E. | N.E. | N.E. |
| Propane | N.E. | N.E. | 1000 ppm | N.E. |
| Diethylene Glycol Monobutyl Ether | 10 ppm | N.E. | N.E. | N.E. |
| Oils, pine | N.E. | N.E. | N.E. | N.E. |
| Zinc bis[O,O-bis(2-ethylhexyl)] bis (dithiophosphate) | N.E. | N.E. | N.E. | N.E. |
| Phosphorodithioic Acid, O,o-di-c1-14-alkyl Esters, Zinc Salts | N.E. | N.E. | N.E. | N.E. |
| Distillates (Petroleum) Solvent-dewaxed Heav Paraffinic | y 5 mg/m3 | N.E. | 500 ppm | N.E. |

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

ENGINEERING CONTROLS: No data available

Personal Protection

EYE/FACE PROTECTION: Wear goggles/face shield. Chemical safety goggles should be worn where contact is possible.

SKIN PROTECTION: Wear impervious gloves to prevent skin contact.

RESPIRATORY PROTECTION: Seek advice from local supervisor. In case of inadequate ventilation use suitable respirator.

7706 Page 3 / 8

HYGIENIC PRACTICES: When using do not smoke. Observe good industrial hygiene practices.

9. Physical and Chemical Properties

Appearance:

Physical State: Liquid

Form: Spray Aerosol

Color: Black

Odor: No data available
Odor Threshold: No data available
pH: No data available
Freeze Point, °C: No data available

Boiling Point, °C: 7
Flash Point, °C: -104

Flammability (solid, gas):

Evaporation Rate:

Combustibility:

No data available

No data available

Supports Combustion

 Explosive Limits, %:
 0.5 - 10.0

 Vapor Pressure @20°C, PSI:
 37-57

Vapor Density: No data available

Relative Density: 0.773

Solubility in Water:

Partition Coefficient, n-octanol/water:

Auto-Ignition Temperature, °C:

No data available

10. Stability and Reactivity

REACTIVITY: Not reactive under normal conditions of use. STABILITY: Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: No data available

CONDITIONS TO AVOID: Keep away from heat, sparks, flames, and other sources of ignition. Do not puncture or incinerate containers. Dropping containers may cause bursting.

INCOMPATIBILITY: No data available

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may produce carbon dioxide and carbon monoxide.

11. Toxicological Information

Information on Likely Routes of Exposure

SKIN CONTACT EFFECTS: May cause an allergic skin reaction (sensitization) with itching, redness and hives.

EYE CONTACT EFFECTS: Contact may cause severe irritation with redness, tearing and pain.

INHALATION EFFECTS: Inhalation of high concentrations of mists may cause irritation of the nose throat and upper respiratory tract.

INGESTION EFFECTS: Aspiration into the lungs during ingestion or vomiting may cause serious lung damage which may be fatal.

7706 Page 4 / 8

Carcinogenicity: contains 1 component (Distillates (Petroleum) Solvent-dewaxed Heavy Paraffinic) present at a level greater or equal to 0.1% that have been identified as possible carcinogenic to humans by IARC (Group 2B).

The following values are calculated based on chapter 3.1 of the GHS document. The product itself has not been tested.

ATE ORAL 8,799 mg/kg

ATE DERMAL 9,103 mg/kg

ATE INHALATION Not classified for acute toxicity based on available data.

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

| <u>CAS-No.</u> 64742-47-8 | <u>Chemical Name</u> Distillates (Petroleum), Hydrotreated Light | Oral LD50 5,000 mg/kg | Dermal LD50 5000 mg/kg | <u>Vapor LC50</u> >100 mg/l |
|------------------------------|--|--------------------------|---------------------------|-----------------------------|
| 74-98-6 | Propane | 5,000 mg/kg | 5,000 mg/kg | 100 mg/l |
| 112-34-5 | Diethylene Glycol Monobutyl Ether | 2,410 mg/kg | 2,764 mg/kg | 100 mg/l |
| 8002-09-3 | Oils, pine | 5,000 mg/kg | 5,000 mg/kg | 100 mg/l |
| 4259-15-8 | Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) | 3,100 mg/kg | 5,000 mg/kg | 100 mg/l |
| 68649-42-3 | Phosphorodithioic Acid, O,o-di-c1-14-alkyl Esters, Zinc Salts | 5,000 mg/kg | 5,000 mg/kg | 100 mg/l |
| 64742-65-0 | Distillates (Petroleum) Solvent-dewaxed Heavy Paraffinic | 5,000 mg/kg | 5000 mg/kg | 100 mg/l |

N.I. = No Information

Skin Corrosion & Irritation:

Product: No data available

Serious Eye Damage & Irritation:

Product: No data available

Components:

Diethylene Glycol Monobutyl Ether 112-34-5 Causes serious eye irritation.

Phosphorodithioic Acid, O,o-dic1-14-alkyl Esters, Zinc Salts 68649-42-3 Causes serious eye irritation.

Zinc bis[O,O-bis(2-ethylhexyl)] bis (dithiophosphate) 4259-15-8 Causes serious eye irritation.

Respiratory or Skin Sensitization:

Product: No data available

Components:

Oils, pine 8002-09-3 May cause an allergic skin reaction.

STOT-Single Exposure:

Product: No data available

STOT-Repeated Exposure:

Product: No data available

Aspiration Hazard:

Product: No data available

Components:

Distillates (Petroleum), Hydrotreated 64742-47-8 May be fatal if swallowed and enters airways.

Oils, pine 8002-09-3 May be fatal if swallowed and enters airways.

7706 Page 5 / 8

Carcinogenicity:

Product: No data available

Reproductive Toxicity:

Product: No data available

Germ Cell Mutagenicity:

Product: No data available

12. Ecological Information

ECOLOGICAL INFORMATION: No data available

PERSISTENCE: No data available
BIOACCUMULATE: No data available
MOBILITY IN SOIL: No data available
OTHER ECOLOGICAL: No data available

13. Disposal Information

DISPOSAL INFORMATION: Consult with your local, regional and federal agencies for information on proper disposal. **CONTAMINATED PACKAGING:** Consult with your local, regional and federal agencies for information on proper disposal.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No data available

DOT

UN Number: UN1950

Proper Shipping Name: AEROSOLS, FLAMMABLE

Technical Name: N/A

Hazard Class(es)

Class: 2.1
Subsidiary Risk N/A
Packing Group: N/A

IATA

UN Number: UN1950

Proper Shipping Name: AEROSOLS, FLAMMABLE

Technical Name: N/A

Hazard Class(es)

Class: 2.1
Subsidiary Risk: N/A
Packing Group: N/A

IMDG

UN Number: UN1950

Proper Shipping Name: AEROSOLS, FLAMMABLE

Technical Name: N/A

Hazard Class(es)

Class: 2.1
Subsidiary Risk: N/A
Packing Group: N/A

7706 Page 6 / 8

The classification shown In this section may be eligible for use of an exception, such as 'Limited Quantity', per the dangerous goods regulations. The shipper of this product should consult the applicable mode's regulation for the UN number displayed above to determine if any exceptions are available and may be utilized, at the shipper's discretion.

15. Regulatory Information

CHEMICAL INVENTORY STATUS:

TSCA On or in compliance with the inventory

DSL All ingredients in this product are listed on the DSL or are exempt.

CALIFORNIA PROPOSITION 65 CARCINOGENS AND REPRODUCTIVE TOXINS:

No Proposition 65 chemicals present or warning required.

16. Other Information

Revision Date: 10/23/2023

Datasheet produced by: Regulatory Department

Legend

- N/A. Not Applicable, N.E. Not Established, N.D. Not Determined, N.I. No Information
- TLV Threshold Limit Values (TLVs®), as established by the American Conference of Governmental Industrial Hygienists (ACGIH®)
- PEL Permissible Exposure Limit, as established by the U.S. Occupational Safety and Health Administration (OSHA), as amended
- TSCA U.S. Toxic Substance Control Act
- DSL Canada Environmental Protection Act: Domestic Substance List

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where the product use and frequency of exposure exceeds that established for the labeled consumer use.

Further Information

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the manufacturer's and seller's control. Purchaser and user are responsible for determining the suitability of the product for a particular purpose, adopting precautions for the protection of property and persons, and compliance with all Federal, State, Provincial, and Local laws.

7706 Page 7 / 8

7706 Page 8 / 8